



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/773,583	02/05/2004	Douglas A. Larson	501296.01 (30266/US)	6732
27076 7590 11/30/2009 DORSEY & WHITNEY LLP INTELLECTUAL PROPERTY DEPARTMENT Columbia Center 701 Fifth Avenue, Suite 6100 SEATTLE, WA 98104-7043			EXAMINER DOAN, DUC T	
			ART UNIT 2185	PAPER NUMBER
			MAIL DATE 11/30/2009	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 10/773,583	Applicant(s) LARSON ET AL.	
	Examiner DUC T. DOAN	Art Unit 2185	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 29 June 2009.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 40-43 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 40-43 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413) |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____ |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

In view of the Appeal Brief filed on 3/24/2008, PROSECUTION IS HEREBY REOPENED. A new ground of rejection is set forth below.

To avoid abandonment of the application, appellant must exercise one of the following two options:

(1) file a reply under 37 CFR 1.111 (if this Office action is non-final) or a reply under 37 CFR 1.113 (if this Office action is final); or,

(2) initiate a new appeal by filing a notice of appeal under 37 CFR 41.31 followed by an appeal brief under 37 CFR 41.37. The previously paid notice of appeal fee and appeal brief fee can be applied to the new appeal. If, however, the appeal fees set forth in 37 CFR 41.20 have been increased since they were previously paid, then appellant must pay the difference between the increased fees and the amount previously paid.

A Supervisory Patent Examiner (SPE) has approved of reopening prosecution by signing below:

Status of Claims

Claims 1-43 have been presented for examination in this application.

Claims 1-39 have been canceled.

Claims 40-43 are rejected.

Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claims 40-43 are rejected under 35 U.S.C. 103(a) as being unpatentable over Zimmerman (US 2005/0105350) in view of Zumkehr (US 6901494) and evidentiary reference (Micron 1Gb: x4, x8, x16 DDR RAM, hereby Micron).

As in claim 40 , Zimmerman discloses a method for executing read and write commands in a memory system having a memory bus (Fig 2, par. 17), issuing a read command to access a first memory location in the memory system (Fig 2, par. 3 host and controller accesses/read data in memory SDRAM); retrieving read data from the first memory location (Fig 2, par. 3 and 14, a first data is read from a first location of device DRAM); receiving the read data on the bidirectional memory bus from the memory system (Fig 2, par. 3 and 14, a first data is read from a first location of device DRAM from module 120); and providing the write data to the memory bus (Fig 2, par. 3 and 14, write a second data to a second location of device DRAM via 112 122).

Zimmerman does not expressly disclose the claim's bidirectional. However, Goodwin discloses a mechanism in which multiple memory devices, i.e expansion devices are connected to a bidirectional bus as shown in Goodwin's Fig 2. It would have been obvious to one of ordinary skill in the art at the time of invention to include bi directional bus as suggested by Goodwin in Zimmerman's system thereby further allows read and write data in the devices to be transferred effectively over the same bidirectional data bus (Goodwin's column 1 lines 10-35). Zimmerman and Goodwin do not expressly disclose the claim's details associating to scheduling a write command after a read command and bypassing data. However, Zumkehr discloses before completion of the read command, scheduling a write command to write data to a second memory location in the memory system (col. 3 lines 40-50, the pipeline of operations means that a subsequent command is scheduled even before completion of a previous command); prior to receiving the read data on the memory bus from the memory system, providing write data corresponding to the write command to the bidirectional memory bus of the memory system (col. 3 lines 40-50, the pipeline of a write command means write data is provided even before completion of a previous command; Fig 5A and 5B show examples of a read command and a write command both requesting large burst of data. A scenario based on Fig 5B comprise a read command follows by a write command of small amount of data, for example one clock cycle of data, can be as followed:

Examiner note: the Fig 5A and 5B illustrates the access to memory device with a **latency** of 3 clocks, i.e time delay from issuing the read command to SDRAMs memory

Art Unit: 2185

devices at the third clock, i.e Fig 5B shows as a read command from hub to sdram at T2B first block, to the read data returning by the SDRAMs of the memory system at the sixth clocks. Of course, the actual latency value can be larger and as such write command and/or additional write data can be pipelined/ provided to memory system during this latency time/window, before the read data returning by the memory system to the controller. Examiner note: definition of latency of memory is commonly known and defined as time from the read command issues to the memory device until the memory device return the read data, see micron page 13. Micron teaches that the read latency is based on delay time TRCD time which can be mapped into several clocks cycles.

This definition of latency is consistent with the definition provided by Applicant who states " **..the latency problem...** More specifically, when a memory device read command is coupled to a system memory device, such as a synchronous DRAM ("SDRAM") device, **the read data are output from the SDRAM device only after a delay of several clock periods**. Therefore, although SDRAM devices can synchronously output burst data at a high data rate, **the delay in initially providing the data** can significantly slow the operating speed of a computer system using such SDRAM devices", see specification's page 2 lines 16-24.

Therefore assuming a device with a read latency of 5 clocks and using the timing based on Fig 2B, a read command at clock 1, i.e T1B first block, which means the corresponding read data is not returning until at least the eight clock cycle, i.e at T4B first block. This is a large timing window which certainly large enough to allow two write

Art Unit: 2185

commands in a pipeline manner on the rambus at the second clock and third clock on the rambus and two corresponding data respectively on the sdram data bus at clock 5 and 6. The arrival of second write command pushing/allowing the first write data corresponding to the first write command to SDRAM at clock 6, i.e T3B first block. Because the read data is not returned at least until the clock 8, therefore it's clear that the first write data is provided prior to receiving the read data as recited in the claim's limitation).

Zumkehr further discloses in the system memory, bypassing the read data on the bidirectional memory bus (Fig 3. col. 5 lines 35-45, shows data is stored in write-buffer 330 thus allowing read data 340 going through);

It would have been obvious to one of ordinary skill in the art at the time of invention to include the memory controller hub circuits and methods as suggested by Zumkehr in Zimmerman's system to allow transferring read data while temporary storing write data, thereby resulting in more efficiently usage of the memory bus in the system (Zumkehr's column 6 lines 35-60; read and write data transferring through the same bidirectional data bus Fig 3: #350 data signals).

As in claim 41, Zimmerman and Goodwin do not expressly disclose the claim's bypass. However, Zumkehr further discloses wherein bypassing the read data on the memory bus comprises decoupling the write data from the memory bus for a time period to avoid data collision on the memory bus (col. 5 lines 35-45, Fig 3, data is stored in write-buffer 330 thus allowing read data 340 going through). It would have been obvious to one of ordinary skill in the art at the time of invention to adopt the teaching of

Art Unit: 2185

Zumkehr in Zimmerman's system modified by Goodwin for the same reasons stated above.

As in claim 42, Zimmerman and Goodwin do not expressly disclose the claim's bypass. However, Zumkehr further discloses temporarily storing the write data in a bypass buffer during the receipt of the read data (col. 5 lines 35-45, Fig 3, data is stored in write-buffer 330 thus allowing read data 340 going through). It would have been obvious to one of ordinary skill in the art at the time of invention to adopt the teaching of Zumkehr in Zimmerman's system modified by Goodwin for the same reasons stated above.

As in claim 43, Zimmerman discloses wherein providing the write data to the memory bus comprises providing the write data through at least one memory module of the memory system (Fig 2 write data must go through memory module 130). Zimmerman and Goodwin do not expressly disclose the claim's decoupling. However, Zumkehr further discloses write data is going through a hub/translation hub (Fig 2 220) before decoupling the write data from the memory bus (Figs 2 and 3, write data is stored/decoupling from the memory bus). It would have been obvious to one of ordinary skill in the art at the time of invention to adopt the teaching of Zumkehr in Zimmerman's system modified by Goodwin for the same reasons stated above.

(10) Response to Argument

Applicant's arguments in response to the last office action have been fully considered but they are not persuasive. Examiner respectfully traverses Applicant's arguments for the following reasons:

A) Applicant's arguments regarding the rejection of claim 40 under U.S.C 35 103(a) have been fully considered but they are not persuasive.

A0) Applicant argues that the cited references do not teach "the data bypass capabilities when a read command is issued, and before the **read latency** is met, **issuing** a write command and corresponding write data".

Examiner contends that Applicant is arguing limitations that are not in the claims. The read latency of a memory device that Applicant referring to in his argument, is well known in the art and it means the time period of several clock cycles, from the memory device received the read command (at the first clock cycle) until it provides the beginning of read data (at the n clock cycle. Data continues to be transferred in additional clock cycles, then the execution of the read command is completed). The present invention does not claim or have any limitation regarding read latency and/or requiring "**issuing** of a subsequent write command and before the **read latency** is met" as argued. Instead the claim 40 recites "before completion of the read command, scheduling a write command..". Scheduling a write command indicates the intention to issue a write command at any time subsequently. In other words, **the scheduling event of a write command is not the same as the issuing event of a write command**, and the issuing of the write command can be issued any time subsequently. Thus claim 40

Art Unit: 2185

intends to cover a much broader period of time than allowing the write command to be issued, much longer than the “before read latency is met” period. In fact, Applicant does not have any “read latency” limitation recited in the claim, perhaps and conveniently to cover a time period larger than the “read latency” period.

As discussed above, Applicant is arguing limitations that are not in the claims, this is a frivolous argument, and therefore the argument is not persuasive.

Claim 40 at best, as a whole, describes the overlapping of a read command operation and a subsequent write command operation, wherein the write command can be issued anytime during and **before the read command operation is completed**, as discussed above.

Specifically, claim 40 describes before the read command operation is completed, then scheduling a write command to write data (“before completion of the read command, schedule a write command..”), and only requires “receiving the read data on the bidirectional memory bus from the memory system; and providing the write data to the bidirectional memory bus”.

Thus at best, the recited claim is interpreted such that when a write command is issued, in a pipelining manner, at a time between a read command is issued (by the memory controller) and the time the read data completely arrived at the memory controller, this write command would meet the limitations recited in the claim.

Zumkehr teaches such memory system as shown in Fig 5B. As stated in the rejection of claim 40, a scenario based on Zumkehr Fig 5B timing diagram that teaches “prior to receiving the read data on the memory bus providing a write data ..providing

Art Unit: 2185

write data corresponding to the write command.." , wherein a read command follows by a write command of small amount of data, for example one clock cycle of data, can be as followed:

Examiner note: the Fig 5A and 5B illustrates the access to memory with a **latency** of 3 clocks, i.e time delay from issuing the read command to SDRAMs memory devices at the third clock, i.e read command from hub to sdram at T2B first block, to the read data returning by the SDRAMs of the memory system at the sixth clocks. Of course, the actual latency value can be larger and as such additional write commands and/or additional write data can be pipelined/ provided to memory system during this latency time/window before the read data returning by the memory system to the controller. Examiner note: definition of latency of memory is commonly known and defined as time from the read command issues to the memory device until the memory device return the read data, see micron. Micron teaches that the read latency is based on delay time TRCD time which can be mapped into several clocks cycles.

This definition of latency is consistent with the definition provided by Applicant who states " **..the latency problem...** More specifically, when a memory device read command is coupled to a system memory device, such as a synchronous DRAM ("SDRAM") device, **the read data are output from the SDRAM device only after a delay of several clock periods.** Therefore, although SDRAM devices can synchronously output burst data at a high data rate, **the delay in initially providing the data** can significantly slow the operating speed of a computer system using such SDRAM devices", see specification's page 2 lines 16-24.

Therefore assuming a device with a read latency of 5 clocks and using the timing based on Fig 2B, a read command at clock 1, i.e T1B first block, which means the corresponding read data is not returning until at least the eight clock cycle, i.e at T4B first block. This is a large timing window which certainly large enough to allow two write commands in a pipeline manner on the rambus at the second clock and third clock on the rambus and two corresponding data respectively on the sdram data bus at clock 5 and 6. The arrival of second write command pushing/allowing the first write data corresponding to the first write command to SDRAM at clock 6, i.e T3B first block. Because the read data is not returned at least until the clock 8, therefore it's clear that the first write data is provided prior to receiving the read data as recited in the claim's limitation.

In other words, because the read latency is several cycles, a large timing window, that sufficiently allows two write commands including sending data of a write command in the bypass buffer to memory device as required in the claim.

Examiner submits that the above scenario of Zumkehr is sufficiently to teach the main Applicant's argument that Zumkehr does not teach "...a write data can not be provided prior to receiving the read data.."

A1) Regarding Applicant's arguments of item D in the Appeal Brief, dated 3/24/2008, the arguments are not persuasive.

First, Applicant continues to argue about the "read latency" that is not in the claim, as discussed in item A0 above;

Second, Examiner contends that Applicant mischaracterize Zumkehr's teaching regarding the "read latency".

Applicant argues "...In contrast, Fig 5B, which includes a write buffer in the translator hub, shows that a new write command 520B following a read command 501B can be issued before the read latency of the previously issued read command 501B is met....However, the write data 527B associated with the new write command 530B remains in the memory and cannot be issued until *after* the read latency of the previously issued read command 501B is met.." and Applicant concludes "Therefore, the Zumkehr reference does not disclose or fairly suggest data bypass capabilities when a read command is issued, and before the read latency is met, issuing a write command and corresponding write (sic).

It's not clear what "issuing a write command and corresponding write" means. Examiner assumes that Applicant intends to state "issuing a write command and corresponding write data". Thus apparently Applicant misinterprets Zumkehr's teaching of the read latency value being used for write commands, and thereby Applicant further asserting that the subsequent write command and corresponding write command must occur before the ending of the previous read command operation. Although Examiner does not agree with Applicant's assertion and the mischaracterization of Zumkehr's teaching, Examiner points out that Zumkehr's teaching of read latency and providing the corresponding write data before the read data as recited in the claim is discussed in details in item A0 above.

Art Unit: 2185

Finally, Applicant point to Zumkehr's col. 4 lines 45-68 to col. 5 lines 1-23, Zumkehr "read latency" time period is referred to be used by specific memory controller logic so that it can pace apart sending out subsequent command operations. Thus this pacing time period may be arbitrary chosen mainly to satisfy pacing requirement of a specific controller/protocol (Rambus memory controller protocol). Realizing that for an actual write operation of a memory device, for example SDRAM memory device, this "read latency" period is not necessary. Zumkehr teaches of using temporary buffering of write data and bypassing circuitry such that read data and write data of several read and write operations can be bypassing and operate in a concurrently manner. By combining with pipelining, this pacing period can be eliminated completely (Zumkehr's column 2 line 61 to column 3 line 50 further teaches that this pacing delay/defer timing **requirement ("read latency") for the write operation of a specific memory controller can be reduced and eliminated (i.e met, no longer required)**). In other words, Zumkehr teaches that by pipelining several read and write commands/operations, and providing buffers to temporary storing write commands and their associating data, such that these write commands and their data can be written concurrently to multiple memory devices, thereby effectively, the pacing time period is eliminated. Zumkehr's teaching of buffering data for bypassing data can be readily applied to any system memory, and any memory devices, and memory controllers, see Zumkehr's column 3 lines 35 to 50.

Art Unit: 2185

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Duc T. Doan whose telephone number is 571-272-4171. The examiner can normally be reached on M-F 8:00 AM 05:00 PM. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Sanjiv Shah can be reached on 571-272-4098. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

/Duc T Doan/

Examiner, Art Unit 2185

/Sanjiv Shah/

Supervisory Patent Examiner, Art Unit 2185